



Bringing Quality & Excellence

IM Supply BV
 Aquamarijnstraat 100-104
 7554 NT Hengelo
 The Netherlands

T: +31 (0)74 291 9294
 F: +31 (0)74 256 6490
 E: info@im-supply.com
 I: www.im-supply.com

TECHNICAL DATA SHEET

JET-LUBE® Extreme® Mud-Resistant Drill Collar & Tool Joint Compound

DESCRIPTION

The EXTREME version of Kopr-Kote is a mud-resistant drill collar and tool joint compound. Premium-quality, non-Lead compound blended with a new, high-temp complex base grease of Jet-lube design. This base grease offers the additional advantages of superior adhesion, improved extreme pressure and anti-wear properties. It also has excellent resistance to water wash-off as well as rust and corrosion protection in the presence of high pH muds. The EXTREME solids content is formulated to prevent excessive circumferential makeup by increasing the coefficient of friction under compressive forces. As stress levels increase above 50% of yield, the friction factor increases, limiting downhole makeup. Full hydraulic joint efficiency is maintained allowing joint shoulder faces to mate completely without standoff.

ADVANTAGES

- Highly resistant to drilling muds.
- Contains no Lead or Zinc.
- EP additives provide anti-galling properties.
- Complex base grease with superior rust and corrosion protection.
- Sticks to wet joints.
- Brushable and stable over wide temp range.
- Consistent rig floor makeup
- Unequaled resistance to downhole makeup.

APPLICATIONS:

EXTREME should be utilised with the torque charts in API RP7G for optimum performance on API drill string connections, or by contacting the drill pipe and connector manufacturer.

NB: Premium drill string connections such as Hi-Torque (HT), eXtreme Torque (XT) and XT-M utilise makeup torques based on thread compound friction factors 1,0. Adjusting makeup torque based on thread compound friction factor may still be advised.

PRODUCT CHARACTERISTICS

Service Ranges:	-0°F (-18°C) to 450°F (232°C)
Thickener:	Complex Soap
Fluid Type:	Petroleum
Dropping Point (ASTM D-2265):	>232°C (450°F)
Specific Gravity:	1,20
Oil separation:	<3,0
Penetration @25°C (IP50/ASTM D-217):	310 - 330
NLGI grade:	1
Copper Strip Corrosion (ASTM D-4048):	1A typical
4-Ball Weld Point (ASTM D-2596), kgf:	1.000
Flash Point (ASTM D-92):	>232°C (450°F)
Friction Factor(Relative to API RP 7G):	1,15

PACKAGING

Code	Net contents	Container
76344664	5kg	Pail
52062339	12,5kg	Pail
13233723	20kg	Pail

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Jet-Lube House

Reform Road • Maidenhead • Berkshire • SL6 8BY

Telephone: +44 (0) 1628 631913 • Fax: +44 (0) 1628 773138 • Internet: www.jetlube.co.uk