**IM Supply BV** 

Aquamarijnstraat 100-104 7554 NT Hengelo The Netherlands T: +31 (0)74 291 9294 F: +31 (0)74 256 6490

E: info@im-supply.com I: www.im-supply.com

25 mm

# TECHNICAL DATA SHEET

## MAGIC Wrench™ Super Penetrant

#### **DESCRIPTION**

MAGIC WRENCH super penetrant attacks rust and corrosion quickly and safely to free corroded parts, loosen nuts and aid in the disassembly of mechanical components. Versatile synthetic formula penetrates, lubricates, removes moisture and frees fasteners, cables, slides and other moving parts. Silicone free. Non-evaporative. Safe on all metals and plastics. Excellent for both food grade and non-food grade applications. Low VOC (Volatile Organic Components) formula assures not only an environmentally responsible product, but more active ingredients to enhance product performance.

### **ADVANTAGES**

- NSF H-1 Authorised.
- · Penetrates fast.
- · Synthetic fluids.
- · Destroys rust.
- · Lubricates.
- · Safe on metal & plastic.
- · Low VOC formula.
- · Silicone free.
- Ozone Safe.
- · Non-flammable (in bulk)
- · Non evaporative.

## **APPLICATIONS:**

MAGIC WRENCH is a premium, synthetic product that may be used on food processing machinery such as chain linkages, cams and slides, stirrups on bottle filing machines, valves, pins, hinges and cables etc. In addition, MAGIC WRENCH is an ideal product for the lubrication and conditioning of air tools.

## PRODUCT CHARACTERISTICS

-51°C (-60°F) to Service range: 177°C (350°F) Clear, pale yellow Appearance: Fluid Type: Ester, PAO & White Oil: Ester, PAO & White Oil Propellant: Hydrocarbon 32 ISO Viscosity Grade: SAE Viscosity Grade: 10 0,84 (Bulk) Specific Gravity: 0,83(Aerosol) 232°C (450°F) Flash Point (ASTM D-92): Copper Strip Corrosion(ASTM D-130): 1B Pour Point (ASTM D-97): -12°C (10°F)

NB: Do not spray directly onto hot surfaces

Spray Pattern (from 300mm distance):

## **PACKAGING**

Code	Net contents	Container
37708733	369g	Aerosol
66825999	473ml	Trigger Spray
54270954	51	Tin
38644153	251	Poly

## LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Telephone: +44 (0) 1628 631913 • Fax: +44 (0) 1628 773138 • Internet: www.jetlube.co.uk