



Bringing Quality & Excellence

IM Supply BV
 Aquamarijnstraat 100-104
 7554 NT Hengelo
 The Netherlands

T: +31 (0)74 291 9294
 F: +31 (0)74 256 6490
 E: info@im-supply.com
 I: www.im-supply.com

TECHNICAL DATA SHEET

MARINE Mp Multipurpose Grease

DESCRIPTION

MARINE-MP

is a mixed soap (calcium-lithium) grease that is ideal for a multitude of "on-board" applications where both economy and performance are important. This smooth, buttery grease has an operating temperature range of -18°C to 163°C (0°F to 325°F) to provide "single grease" use for a variety of applications.

MARINE-MP

is water resistant, highly tenacious and has excellent resistance to the effects of salt spray, heat, water, oxidation and other adverse conditions common to marine usage. As a result, this product will lower maintenance costs and simplify inventory while providing excellent performance.

CHARACTERISTICS

- Smooth Texture
- Water Resistant
- EP Package
- Pumpable
- Color - Purple

ADVANTAGES

- Pivot Pins.
- Plain Bearings.
- Anchor Cables.
- Anti-Friction Bearings.
- Hoist Lines.

CERTIFICATION

MILITARY SPEC / INDUSTRY CONFORMANCE
 14 oz. Cartridge - 915000103CARD

PRODUCT CHARACTERISTICS

Colour:	Purple
Thickener Type:	Lithium/Calcium
Base Oil Type:	Petroleum
Specific Gravity, Typical:	0.96
Density (kg/liter), Typical:	0.96
Flash Point (ASTM D-92):	>221°C (430°F)
Shell 4 Ball (ASTM D-2596)	
Weld Point, kgf:	250
Load Wear Index:	28

Wear Scar Diameter (ASTM D-2266):	0.675
Dropping Point (ASTM D-566):	>175°C (350°F)
Copper Strip Corrosion (ASTM D-4048):	1B
Water Spray Off Resistance (ASTM D-4049):	< 40%
Base Oil Viscosity, Typical:	ISO 220
Timken OK Load, Typical:	55 Lbs.

PACKAGING

Code	Net contents	Container
41216194	400g	Cartridge
55056656	1kg	Tub
60989208	5kg	Pail
17093682	12,5kg	Pail
12979639	181,4kg	Drum

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Jet-Lube House

Reform Road • Maidenhead • Berkshire • SL6 8BY

Telephone: +44 (0) 1628 631913 • Fax: +44 (0) 1628 773138 • Internet: www.jetlube.co.uk