



Bringing Quality & Excellence

IM Supply BV
 Aquamarijnstraat 100-104
 7554 NT Hengelo
 The Netherlands

T: +31 (0)74 291 9294
 F: +31 (0)74 256 6490
 E: info@im-supply.com
 I: www.im-supply.com

TECHNICAL DATA SHEET

MARINE Wire Rope & Hawser Grease™ Lubricant & Protectant

DESCRIPTION

MARINE WIRE ROPE & HAWSER GREASE™ is an economical high performance lubricant for wire rope, hawser and related applications requiring a water resistant, tenacious product that resists the effects of fresh and salt water spray, oxidation, humidity, heat and other adverse conditions common to marine and heavy industrial applications. MARINE WIRE ROPE & HAWSER GREASE maintains and extends the life and performance of wire rope by providing a nondrying film on the outside of the wire rope. This film protects wire rope from corrosion while lubricating the inner strands, drums and sheaves.

- White/Beige Color
- High Temperature
- Anti-Corrosive
- Protects
- NLGI Grade 2
- Nonstaining
- Water Resistant
- Lubricates
- Nondrying

APPLICATIONS:

Recommended for all marine and industrial wire rope, hawser and related activities such as shipyard gantry cranes, mast hoisting cables, loading cranes, offshore rig anchor cables, crane and drag lines, elevator hoist lines or any wire rope cable that operates in harsh conditions.

CERTIFICATIONS

Meets or exceeds requirements of U.S. Military Specification Mil-G 18458B (SH).

OPERATING RANGE
 -18°C to 163°C 0°F to 325°F

PRODUCT CHARACTERISTICS

Thickener:	Lithium
Fluid Type:	Petroleum Oil
Colour/Appearance:	White/Beige Sticky Grease
Dropping Point (ASTM D-2265):	199°C (390°F)
Density (kg/liter), Typical:	0.95
Specific Gravity, Typical:	0.95
Flash Point (ASTM D-92):	>221°C (439°F)

Additives:	Boundary Lubricants, Polymers, R&O
Cone Penetration (ASTM D-217):	265 - 295
Copper Strip Corrosion (ASTM D-4048):	1B
4-Ball Weld Point:	315 Min.
Base Oil Viscosity:	ISO 220, Typical
Oil Separation (Fed. Std. 791 M 321.2):	5% Max.
Volatile Matter:	Less than 2.0%

PACKAGING

Code	Net contents	Container
84878564	12,5kg	Pail
32808872	15,9kg	Pail
58187944	181kg	Drum

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Jet-Lube House

Reform Road • Maidenhead • Berkshire • SL6 8BY

Telephone: +44 (0) 1628 631913 • Fax: +44 (0) 1628 773138 • Internet: www.jetlube.co.uk