



Bringing Quality & Excellence

**IM Supply BV**  
 Aquamarijnstraat 100-104  
 7554 NT Hengelo  
 The Netherlands

T: +31 (0)74 291 9294  
 F: +31 (0)74 256 6490  
 E: info@im-supply.com  
 I: www.im-supply.com

# TECHNICAL DATA SHEET

## SILVER Plus Regular Grade Anti-Seize and Thread Lubricant

### DESCRIPTION

#### SILVER PLUS REGULAR

metallic anti-seize is designed to provide a protective film against galling and seizure over a wide range of applications. The micro-sized particles produce a smooth creamy consistency and allows it to quickly and easily coat fine threaded and small and large-diameter fasteners.

SILVER PLUS REGULAR utilizes a water resistant, high temperature complex grease base as its carrier giving it superior "stay-put" qualities. The complex thickener and highly refined base fluids allow for brushability from -29°C (-20°F) to 232°C (450°F). The petroleum carrier, however, makes SILVER PLUS REGULAR unsuitable for oxygen service.

#### SILVER PLUS REGULAR

contains micro-sized aluminum as well as other nonmetallic extreme pressure and anti-wear particles. The metallic components make it very conductive and since the primary anti-seize particles are aluminum, it nearly eliminates the potential for galvanic corrosion. It also makes it the anti-seize of choice for components made of aluminum and its alloys.

### ADVANTAGES

- Shiny Silver Color.
- Operating Range: -129°C (-65°F) to 982°C (1800°F).
- Brushable from -29°C (-20°F) to 232°C (450°F).
- Resists galvanic corrosion.
- Permits reuse of fittings.
- Resists alkaline and acid vapours.

### APPLICATIONS

#### SILVER PLUS REGULAR

is excellent for use on bolts, nuts, gaskets, pipe fittings, guides and slides, valve assemblies, press fits, cylinder heads, chain drives, pump mountings, forging dies, manway studs, exhaust manifold studs, etc.

### PRODUCT CHARACTERISTICS

Thickener:	Aluminum Complex
Fluid Type:	Highly refined Petroleum
Colour/Appearance:	Silvery, buttery gel
Specific Gravity, Typical:	1.15
Density (kg/liter), Typical:	0.91
Penetration @ 25°C (77°F) (ASTM D-217):	310 - 350
Coefficient of Friction:	0.08
Flash Point (ASTM D-92):	>221°C (430°F)
Copper Strip Corrosion (ASTM D-4048):	1B
Oil Separation, 100°C:	<5%

### PACKAGING

Code	Net contents	Container
32287936	250g	Brush Top Can
68463151	500g	Brush Top Can

### LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



### Jet-Lube House

Reform Road • Maidenhead • Berkshire • SL6 8BY

Telephone: +44 (0) 1628 631913 • Fax: +44 (0) 1628 773138 • Internet: www.jetlube.co.uk